

What is claimed is:

1 1. A seat of a child-care instrument provided with a seat
2 plate and a backrest plate which can be reclined,
3 comprising:

4 a lapping plate integrally having a seat surface
5 portion facing said seat plate and a back surface portion
6 facing said backrest plate, wherein

7 said seat plate and said backrest plate each have
8 first openings penetrating in the thickness direction,

9 said lapping plate has second openings penetrating
10 in the thickness direction, in its seat surface portion
11 and back surface portion and it is provided such that it
12 can be displaced between a first position in which
13 positions of said first and second openings are aligned
14 and a second position in which positions of said first
15 and second openings are shifted, and

16 a plurality of hinge portions extending in the width
17 direction are provided so as to be spaced in the vertical
18 direction, in a corner region connecting the seat surface
19 portion and the back surface portion of said lapping
20 plate.

1 2. The seat of the child-care instrument according to
2 claim 1, wherein said plural hinge portions are formed of
3 thinned portions reduced in thickness of the lapping
4 plate.

1 3. The seat of the child-care instrument according to
2 claim 2, wherein said thinned portion is formed by
3 cutting in a back surface of said lapping plate.

1 4. The seat of the child-care instrument according to
2 claim 1, wherein said lapping plate is provided such that
3 it can be slid along said seat plate and said backrest
4 plate.